



Model		Unit	VMC-650	VMC-850/850B	VMC-850C	VMC-1060
Table size		mm	800X420	950X460/1050X500	1000X530	1300X600
Travel	Longitude (X)	mm	650	800	800	1000
	Crossward (Y)	mm	400	500	500	605
	Vertical (Z)	mm	480	550	700	600
Distance between Spindle and table		mm	80-560	105-655	110-810	180-780
Distance between Spindle and column		mm	480	550	575	600
Spindle	Rotation Speed	rpm	8000/10000*	8000/10000*	8000/10000*	8000
	Taper		BT40	BT40	BT40	BT40/BT50*
	Motor	kw	7.5	7.5	7.5	11
Rapid	Longitude (X)	m/min	10	12	12	12
	Crossward (Y)	m/min	10	12	12	12
	Vertical (Z)	m/min	10	10	10	10
Cutting Feed		m/min	8	8	8	8
Positioning accuracy		m/min	0.008	0.008	0.008	0.008
Min.set moving unit		mm	0.001	0.001	0.001	0.001
Dimension(L*W*H)		mm	2350X2200X2300	2500X2300X2500	2750X2500X2500	3300X2800X2700
Net Weight		kg	4200	5000	6000	7100
Max.load of table		kg	600	600	600	800
Configurable gear head modle	Modle		/	VMC-850G	VMC-1155G	VMC-1060G
	Rotation Speed	rpm	/	low:10-1000 High speed:1001-8000	low:10-1000 High speed:1001-8000	low:10-1000 High speed:1001-8000

Note: "*" Means Optional