



Model	ZX7550CW	ZX6350CW
Spindle taper	ISO30/R8/MT4	MT4(V) ISO40(H)
Distance form spindle to table	70-420mm	300mm
Distance from horizontal to table	-	110-410mm
Distance from spindle to column	-	200-700mm
Spindle speed	(8 step)115-1750rpm(V) (6 step)60-1350rpm(H)	(8 step)114-1750rpm(V) (6 step)40-1300rpm(H)
Spindle travel	120mm	120mm
Max. drillingcapacity of auto-feeding	50mm	M16
Head movement	±45°	±45°
Table size	800x240 mm	1120(1200)x280 mm
Max. weight of workpiece	-	200kg
Table travel(Horizontal/Cross/Vertical)	400/230/350 mm	600/260/300 mm
T-slot Number/Width/Distance	3/14mm/60mm	3/14mm/60mm
Milling head moving(Vertical)	Dovetail	Dovetail
Cross slide way	Dovetail	Dovetail
Longitudinal slide way	Dovetail	Dovetail
Horse power for main motor	0.85/1.5kw(V) 1.5kw(H)	2.2kw(V) 2.2kw(H)
X axis driving motor	370W	370W
Coolant pump power	40W(12L)	-
Overall dimension	1290x1220x2100mm	1660x1340x2130mm
Packing size	1140x1220x2220mm	1620x1400x2220mm
N.W/G.W	850/1000kg	1300/1380kg